

## Dial Thickness Gauge F 50

with lifting device

High resolution while offering a relative large measuring range distinguishes this Dial Thickness Gauge. The lifting device provides the initial measuring force of 1,2 N independent of the user.

In standard execution the Dial Thickness Gauge F 50 will be supplied with feelers form c. When ordering, please state whether you require another form of feelers than form c. The forms of feelers a, b, d or e are available at the same price.

Dial Thickness Gauge F 50 with lifting device	
Reading	0,001 mm
Range	5 mm
Range per revolution	0,2 mm
Bezel-Ø	58 mm
Depth of jaw	50 mm
Accuracy according to works standard	0.0500.9.0001, edition 4/2001 hysteresis fu however not checked
Standard feeler	form c
Optional feelers	forms a, b, d or e

## Spare Dial Gauge for F 50

with lifting device

Spare Dial Gauges for the model F 50 with lifting device will be supplied like all the other Spare Dial Gauges without lifting device and without feeler but with extension 3.2236.

Delivery of a Spare Dial Gauge for F 50 with the upper feeler form a, b, c, d or e at a surcharge.

Spare Dial Gauge for F 50 with lifting device	
Reading	0,001 mm
Range	5 mm
Range per revolution	0,2 mm
Bezel-Ø	58 mm
Stem-Ø	8 h 6
Accuracy according to works standard	0.0500.9.0001, edition 4/2001 hysteresis fu however not checked
Standard feeler	without
Optional feelers	forms a, b, c, d or e

