

## Dial Thickness Gauge J 50

with lifting device

The Dial Thickness Gauge J 50 possesses a lifting device and thus the contact force is independent of the user.

For the model J 50 in standard execution the contact force is 0,8 N. Specials with increased or reduced contact force are available on request with values listed in the table below the illustration.

Dial Thickness Gauge J 50 with lifting device	
Reading	0,01 mm
Range	10 mm
Range per revolution	1 mm
Bezel-Ø	58 mm
Depth of jaw	50 mm
Accuracy according to	DIN 878
	hysteresis fu however not checked
Standard feeler	form c
Optional feelers	forms a, b, d or e

## Spare Dial Gauge for J 50

with lifting device

The Spare Dial Gauge for model J 50 with lifting device will be delivered like all other Spare Dial Gauges without lifting device and feeler but with extension 3.2236.

For a surcharge we will supply the Spare Dial Gauge for J 50 with the upper feeler form a, b, c, d or e.

Spare Dial Gauge for J 50 with lifting device	
Reading	0,01 mm
Range	10 mm
Range per revolution	1 mm
Bezel-Ø	58 mm
Stem-Ø	8 h 6
Accuracy according to	DIN 878
	hysteresis fu however not checked
Standard feeler	without
Optional feelers	forms a, b, c, d or e



Table of Contact Force

Type	Standard Force	Reduced Force	Increased Force
J 50 with lifting device	0,8 N	0,6 N	2,0 N
J 100	0,8 N	0,6 N	2,0 N
J 200	1,5 N	1,2 N	3,0 N
J 200/30	1,5 N	1,2 N	3,0 N

Variants with push-on rod and additional weights on request.